



10 SERIES EXIT DEVICE



Jackson's 10 Series Exit Device is universally recognized as the standard for aluminum storefront hardware. This crossbar device was designed with simplicity in mind, yet it will provide many years of smooth, reliable operation. Available in both a Rim and Concealed Vertical Rod version this device is suitable for use with narrow, medium and wide stile doors. The 10 Series Exit Device is the perfect solution when considering a reliable, maintenance free Exit Device.

TECHNICAL INFORMATION

FEATURES

- Available as Rim and Concealed Vertical Rod.
- Contoured Crossbar
- Available with Push Paddle operation on active side
 - Paddle engraved with "PUSH"
- Extra heavy-duty lever arms and body
- Wear points insulated by nylon sleeves and rollers
- Dual dogging feature
 - By outside cylinder
 - By dogging pins beneath housing
- Concealed fastening for added security
- Easy installation
- UL Listed for Panic Hardware


MATERIALS

- Body and Arm High Tensile Strength Aluminum
- Paddle High Tensile Strength Aluminum
- Crossbar Extruded Aluminum
- Mechanical Components Stainless and Plated Steel
- Top and Bottom Bolts Plated Hardened Steel
- Rim Latch Sintered Steel
- Strikes Sintered Steel

FINISH

- Standard Anodized Finish:
- Dark Bronze - DBZ 313
 - Satin Black - BLK 335
 - Satin Aluminum - US28 / 628


DIMENSIONS - Inch (Metric)





10 SERIES EXIT DEVICE

1085 CONCEALED VERTICAL ROD




APPLICATION:

- 1-3/4" (44.5 mm) Narrow, Medium and Wide Stile Aluminum Doors.
- Product is shipped for use with standard 1-3/4" (44.5 mm) Thick Doors - 2" (51 mm) Door Mounting is optional

FEATURES:

- Non-Handed
- Independent top and bottom bolt action - 1/2" (13 mm) bolt throw.
- Trigger action, positive bolt release
- Adjustable bolt guides allow bolt adjustment with door installed.
- Requires No. 30-821J Cylinder mounting pad when using mortise cylinder for keyed entry.
- Uses standard mortise cylinder with maximum security (MS) type cam. (Supplied by Others)
- Foam rubber silencers to quiet rod operation.
- Standard mounting package consists of machine screw type fasteners.
- Crossbar mounting height 36-1/2" from bottom of door.
- Rod length shipped standard for 7/0 (2134 mm) high doors. For doors over 7/0 (2134 mm) High:
 - Top Rod Extender - 12" (305 mm) No. 30-1347
 - Top Rod Extender - 24" (609 mm) No. 30-1348
- Top & Bottom Bolt No. 30-763P
- Top & Bottom Strikes No. 30-1084

1095 RIM EXIT DEVICE



APPLICATION:

- Aluminum, wood or hollow metal Doors.
- Product is shipped for use with aluminum or hollow metal doors - Wood door mounting is optional.

FEATURES:

- Handed - Not Reversible
- Uses standard rim cylinder for keyed entry - mounting pad not necessary. (Cylinder supplied by others)
- Dual function operation - Field Selectable:
 - Standard - Key removable in unlocked position
 - Optional - Night Latch function
 - Optional - (Key removable in locked position only)
- Adjustable Strike Options:
 - Surface Mounted Strike:
 - Type "C" (Standard) . . . No. 30-2436
 - Surface Mounted for use with Applied or Blade Stop:
 - Type "S" No. 30-2501



10 SERIES EXIT DEVICE

ACCESSORIES



For Doors Over 7/0 (2134 mm) High:
Top Rod Extender - 12" (305 mm) . . . No. 30-1347
Top Rod Extender - 24" (609 mm) . . . No. 30-1348

Top & Bottom Bolt - 1085

No. 30-763P



Mortise Cylinder
Mounting Pad

No. 30-821J




Adjustable
Top & Bottom
bolt guides

Top = No. 30-934

Bottom = No. 30-320

Top & Bottom
Strikes - 2086


No. 30-1084



Bottom



Top



Top Bolt Trip

No. 30-824



Rim Strike Options - 1095


Surface Mounted
Strike - Type "C" (Standard)

No. 30-2436



Surface Mounted for use with
applied or blade stop - Type "S"

No. 30-2501



Concealed Vertical
Rod Silencers

No. 30-1552



Wood Door Mounting Kit
for 1095 Rim Device

No. 30-894

