

INTERMEDIATE OR SIDE JAMB PIVOTS

PIVOTS AND PIVOT SETS

MODEL FA19

Description & Features


- Full mortise
- Behavioral health or high security applications
- Handed
- Optional intermediate pivot for institutional use or installations where flat surfaces are objectionable
- Maintains door alignment
- Aids in installing bottom pivots
- 3/4" (19mm) offset
- Door edges must be beveled in 1/8" in 2"
- Ferrous base material
- Doors 60" (1524mm) to 90" (2286mm) in height should use one intermediate pivot. Each additional 30" (762mm) warrants another intermediate pivot
- Furnished with wood and machine Torx® screws
- Available in plated or sprayed finishes

Compliance

- May be used with fire door assemblies



Technical Information



MODEL M19

Description & Features


- Full mortise
- Handed
- Not load-bearing
- Maintains door alignment
- Aids in installing floor closers and bottom pivots
- 3/4" (19mm) offset
- Door edges must be beveled in 1/8" in 2"
- Non-ferrous base metal
- Doors 60" (1524mm) to 90" (2286mm) in height should use one intermediate pivot. Each additional 30" (762mm) warrants another intermediate pivot
- Furnished with wood and machine screws
- Available finishes: plated (M19, M19-20); plated or sprayed finishes (FM19)

Optional Features

- Available for 1-1/2" (38mm) offset

Compliance

- Available for fire door assemblies (ferrous material) - specify FM19
- For 20-minute label suffix "-20" to the part number
- Cal Fire 3725-0047:0108 (-20 min)



Technical Information

