


Stop Strip



- Aluminum Alloy 6063,
- T5 Temper Pile is Gray. Vinyl, NGP-TPV and Silicone
- are Black 3⁄8" Tall Works in Conjunction With Our Saddle Threshold to Provide a Seal Against the Door, Providing
- Weather Resistance Weight: .16 Lbs. /Ft. #6 Self-Tapping Machine Screws Included











POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS, FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO 1½ HOURS. CATEGORY J


gp.co 1-800-NGP-RUSH

FAX: (800) 255-7874 QUOTES: quotes@ngp.com



INSTALLATION **INSTRUCTIONS**

- 1. Cut threshold to size required.
- 2. Notch around door frame if desired.
- 3. Attach to floor surface with fasteners provided.
- 4. Caulk around base of threshold for moisture control.





FAX: (800) 255-7874 QUOTES: quotes@ngp.com ORDERS: orders@ngp.com

NGP MEMPHIS 4985 East Raines Road

CARSON CITY 3689 Arrowhead Drive Carson City, NV 89706